



आईआरईएल (इंडिया) लिमिटेड
IREL (India) Limited
(Formerly Indian Rare Earths Limited)
(भारत सरकार का उपक्रम)
(A Government of India Undertaking)

CIN : U15100MH1950GOI008187 Website : www.irel.co.in



ISO 9001: 2015, ISO 14001: 2015 & ISO 45001 : 2018 Company

CORRIGENDUM- II

Dated: 14/02/2024

Item/Job Description	Renovation, reconstruction of toilets and a change room for workers at REEP, IREL, OSCOM plant
CPP E-Tender ID:	2025_IREL_222770_1 dated: 04/01/2025

Following Changes are hereby made in the tender:

Sl. No	Page no.	Clause	In Place of	To Read as
1	60/73	BOQ SI No. 24 Providing and fixing factory made single extruded WPC (wood polymer composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (suspension grade) , calcium carbonate and natural fibers (wood powder / rice husk/ wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (face) and 900 N (edge) , minimum compressive strength 50 N/mm ² , modulus of elasticity 850 N/mm ² and resistance to be spread of flame of class A category with property of being termite /borer proof , water proof and fire retardant and fixing with stainless steel butt hinges of required size with necessary full body threaded star headed counter sunk SS screws all as per direction of EIC. 30 MM thick	Unit : Meter	Unit : Sqm
		BOQ SI No. 27 Supplying, providing and fixing of FRP 30mm thick door (+/-2mm tolerance) paneled door shutter made out of fire retardant grade unsaturated polyester resin, moulded to 3mm thick FRP laminate for forming hollow rails and styles, with wooden frame and suitable blocks of seasoned wood inside at required places for fixing of fittings, cast monolithically with 5mm thick FRP laminate for panels. The door to be finished with two coats of approved enamel paint. The door to be fixed with frame with 6 nos of 4 inch hinges with help of 1.25 inch full thread CSK screw, including all steel fittings like door handle, tower bolts, aldrops, etc. complete as per direction of EI	Unit : Cum	Unit : Sqm

2	57/73	<u>BOQ NO: 5</u>	Brickwork with bricks of minimum crushing strength 60kg/cm ² in foundation and plinth in cement mortar 1:6 (1 cement : 6 coarse sand)	Brickwork with bricks of minimum crushing strength 60kg/cm ² with cement mortar 1:6 (1 cement:6 coarse sand) in below and above the pinth level.
3	57/73	<u>BOQ NO: 8</u>	Providing and laying in position machine mixed and machine vibrated cement concrete of M-20 grade reinforced cement concrete , excluding the cost of centering, shuttering and reinforcement as per direction of Engineer-in-charge for all work up to Plinth level.	Providing and laying in position machine mixed and machine vibrated cement concrete of M-20 grade reinforced cement concrete , excluding the cost of centering, shuttering and reinforcement as per direction of EIC. All work below and above the pinth level.

All other terms and conditions of the tender shall remain unchanged. Please visit us at <http://irel.co.in> , www.eprocure.gov.in for other details and further Corrigendum(s), if any.

Sd/-
GM-Tech.(Purchase) & I/C Marketing
