



आईआरईएल (इंडिया) लिमिटेड
IREL (India) Limited
(Formerly Indian Rare Earths Limited)
(भारत सरकार का उपक्रम)
(A Government of India Undertaking)

CIN : U15100MH1950GOI008187 Website : www.irel.co.in



ISO 9001: 2015, ISO 14001: 2015 & ISO 45001 : 2018 Company

CORRIGENDUM- III

Dated: 18/02/2024

Item/Job Description	Renovation, reconstruction of toilets and a change room for workers at REEP, IREL, OSCOM plant
CPP E-Tender ID:	2025_IREL_222770_1 dated: 04/01/2025

Following Changes are hereby made in the tender:

Sl. No	Page no.	Clause	In Place of	To Read as
1	60/73	BOQ SI No. 24 Providing and fixing factory made single extruded WPC (wood polymer composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (suspension grade) , calcium carbonate and natural fibers (wood powder / rice husk/ wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (face) and 900 N (edge) , minimum compressive strength 50 N/mm ² , modulus of elasticity 850 N/mm ² and resistance to be spread of flame of class A category with property of being termite /borer proof , water proof and fire retardant and fixing with stainless steel butt hinges of required size with necessary full body threaded star headed counter sunk SS screws all as per direction of EIC. 30 MM thick	Unit : Meter	Unit : Sqm
		BOQ SI No. 31 Providing and fixing false ceiling at all heights with integral densified calcium silicate reinforced with fibre and natural filler false ceiling tiles of Size 595x595mm of approved texture, design and patterns as per CPWD Specification 2019, to be laid in true horizontal level suspended on inter-locking metal T-Grid of hot dipped galvanised iron section of 0.33mmthick (galvanized @ 120 grams per sqm including both sides)comprising of main-T runners of size 24x38 mm of length 3000 mm,cross - T of size 24x32 mm of length 1200 mm and secondaryintermediate cross-T of size 24x32 mm of length 600mm to formgrid module of size 600 x 600 mm, suspended from ceiling usinggalvanised mild steel items (galvanizing @ 80 grams per sqm) i.e. 12x50 mm long dash fasteners, 6 mm dia fully threaded hanger rod upto 1000 mm length and L-shape level adjuster of size 76x25x25x1.6 mm fixed with grid and Z cleat of size 25x37x25x1.6mm thick	Unit : Cum	Unit : Sqm

		with precut hole on both 25mm flange to pierce into 12x50mm or even bigger size dash fastener if require, fixed with Glavanised iron perimeter wall angle or size 24x24x0.40 mm of length 3000 mm to be fixed on periphery wall / partition with the help of plastic rawl plugs at 450mm center to center and 40 mm long dry wall S.S screws. With 15mm thick tegular edged light weight calcium silicate false ceiling tiles The workshall be carried out as per specifications, drawing and as per directions of the Engineer-in-Charge		
2	57/73	<u>BOQ NO: 5</u>	Brickwork with bricks of minimum crushing strength 60kg/cm ² in foundation and plinth in cement mortar 1:6 (1 cement : 6 coarse sand)	Brickwork with bricks of minimum crushing strength 60kg/cm ² with cement mortar 1:6 (1 cement:6 coarse sand) in below and above the pinth level.
3	57/73	<u>BOQ NO: 8</u>	Providing and laying in position machine mixed and machine vibrated cement concrete of M-20 grade reinforced cement concrete , excluding the cost of centering, shuttering and reinforcement as per direction of Engineer-in-charge for all work up to Plinth level.	Providing and laying in position machine mixed and machine vibrated cement concrete of M-20 grade reinforced cement concrete , excluding the cost of centering, shuttering and reinforcement as per direction of EIC. All work below and above the pinth level.

All other terms and conditions of the tender shall remain unchanged. Please visit us at <http://irel.co.in> , www.eprocure.gov.in for other details and further Corrigendum(s), if any.

Sd/-
GM-Tech.(Purchase) & I/C Marketing
