

Technical Specifications

Sl.No	Technical Specification given as	Technical Specification to be corrected as
01	4Core, 1.5Sq.mm. multi stranded Cu conductor, PVC insulated, PVC inner sheathed, GI steel wire armoured, Overall PVC insulated, 1.1KV graded, cable as per IS 1554. Special Condition: Each meter length shall be marked on the outer surface of the cable along with the ISI marking. Cable shall be supplied in 1000Mtr drum each	Armoured cable, 4C x 1.5Sq.mm. multi stranded Cu conductor, XLPE insulated, PVC inner sheathed, GI flat/round armoured, Overall PVC insulated, 1.1KV graded, cable as per IS 7098. Special Condition: Each meter length shall be marked on the outer surface of the cable along with the ISI marking. Cable shall be supplied in 1000Mtr drum each
02	12Core, 1.5Sq.mm multi stranded Cu conductor, PVC insulated, PVC inner sheathed, GI steel wire armoured, Overall PVC insulated, 1.1KV graded, cable as per IS 694. Special Condition: Each meter length shall be marked on the outer surface of the cable along with the ISI marking. Cable shall be supplied in single length.	12Core, 1.5 Sq.mm multi stranded Cu conductor, PVC insulated, PVC inner sheathed, Overall PVC insulated, 1.1KV graded, flexible cable as per IS 694. Special Condition: Each meter length shall be marked on the outer surface of the cable along with the ISI marking. Cable shall be supplied in single length.